INTERVIEW PURPOSES ONLY

APPENDIX

Changes to Claims:

Claims 45-81 are added.

The following is a marked-up version of the amended claims:

- 12. (Amended) A method according to claim 10, wherein the coating is applied directly to the entire outside surface of the article which is not covered by said predetermined quantity of coating spreading under the effect of centrifugal force.
- 32. (Amended) A method of applying a coating on a hollow article comprising a side wall, the method including the steps of depositing a predetermined quantity of coating in the fluid state on a an inner surface of the article without said coating contacting said side wall, and spreading it by causing the article to revolve, wherein the surface on which the coating is deposited lies inside the article and the quantity of coating deposited is sufficient to enable it to rise under the effect of centrifugal force at least part of the way up the side wall of the article and wherein rotation of the article is stopped suddenly after the coating has spread by the desired amount.

INTERVIEW PURPOSES ONLY

	34.	(Amended) A method of apprying a coating on an article, the method	
including the steps of comprising:			
		depositing a predetermined quantity of coating in the fluid state on a surface	
of the	article,	and and	ſ.
		spreading it the coating by causing the article to revolve; and	Son of
		, wherein the coating is applied applying the coating directly to a surface of	1
the arti	icle whi	ich is not covered by said predetermined quantity of coating spreading under the	
effect o	of centr	ifugal force.	

- 40. (Amended) A method according to claim 3934, wherein rotation of the article is stopped suddenly after the coating has spread by the desired amount.
- 41. (Amended) A method of applying a coating on a hollow article comprising a bottom and a side wall, said bottom having an outer surface and an inner surface, the method including the steps of depositing a predetermined quantity of coating in the fluid state on said outer surface of said bottom, and spreading it the coating by causing the article to revolve, said article being selected from the group comprising a container body, a container lid, a stopper and a flask.
- 42. (Amended) A method of applying a varnish or a paint on a hollow article comprising a bottom and a side wall, the method including the steps of depositing a predetermined quantity of varnish or paint in the fluid state on a center area of said bottom and spaced from said side wall, and spreading it the varnish or the paint by causing the article to revolve.